

▶ **75 ohm Digital Video Coaxial Cable - flexible (L-CFW Series)**

Product Name

75 ohm Digital Video Coaxial Cable - flexible

Model Number

L-CFW Series



Product Image

Flexible Digital Coax Cable.

- HD-Serial Digital Video.
- Mobile Applications.
- HDTV Upgrades.
- Broadband Facilities.
- SMPTE 259M, 292M,424M.
- Solid Copper Center Conductor.
- Foam PE Dielectric.
- Dual Copper Braid for Flexibility.
- 2 Sizes Available.
- Precision Coax 100% Sweep Tested.

MECHANICAL SPECIFICATIONS			
Model	Std. Lng. ft. (m)	Wt. Std. Lng. lbs. (kgs)	Nominal O.D. in. (mm)
L-3CFW	328 (100)	11.24 (5.1)	.228 (5.8)
	656 (200)		
L-5CFW	984 (300)	17.86 (8.1)	.303 (7.7)

(contd.) MECHANICAL SPECIFICATIONS					
Model	Cond. Material AWG	Cond. O.D. in. (mm)	Dielectric Insulation Type*	Insulation O.D. in. (mm)	Shield Material Coverage mm/ends/carriers
L-3CFW	Bare Copper #22	.026 (0.65)	Foam PE	.122 (3.1)	0.12TA/5/24 (94% or more) 0.12TA/6/24 (94% or more)
L-5CFW	Bare Copper #18	.041 (1.05)		.193 (4.9)	0.12TA/7/24 (93% or more) 0.12TA/9/24 (96% or more)

*Dielectric Strength = 1000V AC/1min

ELECTRICAL PERFORMANCE				
Model	Cond. D.C.R. (ohm/100m)	Shield D.C.R. (ohm/100m)	Nom. Cap. @1KHz (pF/m)	Nom. Imp. ohm
L-3CFW	5.5	0.7	17	75
L-5CFW	2.3	0.5	(55)	

Phone: 973-837-0070 Fax: 973-837-0080

Copyright (C) 2009 Canare Corporation of America All Rights Reserved.