


5200FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information
please call

1-800-Belden1



Description

16 AWG bare copper conductors, PP insulation, conductors cabled, Beldfoil® shield tape (foil side out) with drain wire, PVC jacket with ripcord, sequential footage marking every two feet

Suitable Applications (Overall):

Suitable Applications Intercom/PA Systems, Sound/Audio Systems

Physical Characteristics (Overall):

Conductor:

AWG

# Conductors	AWG	Stranding	Conductor Material
2	16	19x29	BC - Bare Copper

Insulation:

Insulation Material

Insulation Material	Wall Thickness (in.)
PP - Polypropylene	0.007

Outer Shield:

Outer Shield Material

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket:

Outer Jacket Material

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.017

Outer Jacket Ripcord Yes

Overall Cabling:

Overall Cabling Lay Length & Direction

Length (in.)	Twists (ft.)
3	4

Overall Cabling Color Code Chart

Number	Color
1	Black
2	Red

Overall Nominal Diameter: 0.18 in.

Mechanical Characteristics (Overall):

Operating Temperature Range -20°C To +75°C

UL Temperature Rating 75°C

Bulk Cable Weight: 30.100 lbs/1000 ft.

Max. Recommended Pulling Tension: 85.500 lbs.

5200FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

Min. Bend Radius (Install)/Minor Axis: 1.800 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

NEC/(UL) Specification	CMR
NEC Articles	800
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	04/01/2005

Flame Test:

UL Flame Test	UL1666 Vertical Shaft
C(UL) Flame Test	FT4

Plenum/Non-Plenum:

Plenum Number	6200FE
---------------	--------

Electrical Characteristics (Overall):

Nom. Inductance

Inductance (µH/ft)
0.140

Nom. Capacitance Conductor to Conductor

Capacitance (pF/ft)
63.250

Nom. Capacitance Cond. to Other Conductor & Shield

Capacitance (pF/ft)
114.000

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
4.000

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
14.400

Max. Operating Voltage - UL

Voltage
300 V RMS

Max. Recommended Current

Current
6.25 Amps per conductor @ 25°C

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5200FE 0081000	1,000 FT	26.000 LB	GRAY	C	2 #16 PP FS FRPVC GRY
5200FE 008500	500 FT	13.500 LB	GRAY	C	2 #16 PP FS FRPVC GRY
5200FE 008U1000	1,000 FT	31.000 LB	GRAY		2 #16 PP FS FRPVC GRY
5200FE 008U500	500 FT	13.500 LB	GRAY		2 #16 PP FS FRPVC GRY
5200FE 009U1000	1,000 FT	31.000 LB	WHITE		2 #16 PP FS FRPVC WHT

Notes:

C = CRATE REEL PUT-UP.

5200FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

Revision Number: 2 Revision Date: 06-02-2008

© 2008 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS), EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.